

Lead Free Full Port Brass Ball Valves



NPT shown here.

Lead Free Full Port Brass Ball Valve

The lead free full port ball valves are forged brass that combine reliable operation with maximum economy. Now with multiagency approvals, the PurePro® full port ball valve is ideal for gas, fuels, fire protection, and general plumbing and HVAC applications including potable water. Valves are ANSI 3rd party Lead Free* certified.


Features

- Lead free materials and certification
- 2 Piece, full port design
- Blowout proof stem design
- Adjustable stem packing nut
- Multiple agency approvals


Performance rating

- Valve design rating:
600 CWP - 1/4" to 2"
- Temperature range:
-20°F to 300°F

Specifications



NPT x NPT



Solder x Solder

Full-Port Brass Ball Valve Mfr #	Size	Dimensions (in.)					Weight (lbs.)
		A	B	C	D	E	
NPT							
PROT101LF-14	1/4"	0.39	1.76	1.73	3.54	--	0.33
PROT102LF-38	3/8"	0.39	1.76	1.73	3.54	--	0.30
PROT103LF-12	1/2"	0.58	2.05	2.04	3.54	--	0.44
PROT104LF-34	3/4"	0.75	2.36	2.26	3.78	--	0.66
PROT105LF-1	1"	0.95	2.76	2.58	4.53	--	1.10
PROT106LF-114	1-1/4"	1.26	3.31	3.05	4.53	--	1.57
PROT107LF-112	1-1/2"	1.58	3.66	3.37	5.42	--	2.40
PROT108LF-2	2"	1.97	4.18	3.70	6.16	--	3.37
SOLDER							
PROC203LF-12	1/2"	0.58	2.05	1.84	3.54	0.63	0.38
PROC204LF-34	3/4"	0.75	2.75	2.14	3.78	0.88	0.64
PROC205LF-1	1"	0.95	3.31	2.45	4.53	1.13	0.99
PROC206LF-114	1-1/4"	1.26	3.82	3.04	4.35	1.38	1.40
PROC207LF-112	1-1/2"	1.58	4.43	3.17	5.39	1.63	2.17
PROC208LF-2	2"	1.97	5.38	3.49	6.31	2.13	2.97

* The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with CA AB1953, VT Act 193, MD HB372, LA HB471 and Federal Public Law 111380. ANSI 3rd party approved and listed.