


PUREPRO® THERMOSTATS

DP721T Touchscreen 7-Day Programmable Thermostat Up to 2 Stage Heat / 1 Stage Cool Conventional or Heat Pump System Power Only

Features:

- Large, dot-matrix TRUE TOUCH-SCREEN with adjustable contrast
- 7-Day PROGRAMMABLE with 4 events per day and a COPY option for each day
- Patented ENERGY WATCH, monitors the KWH consumption and dollar cost of operating the HVAC system
- Filter Monitor feature indicates when to change air filter
- INSTALLER MESSAGE provides handy reminder for service or contact in case of a heating or cooling emergency
- Security feature prevents operating thermostat without entering 4-digit PIN
- AUTOMATIC CHANGEOVER mode - no need to manually switch between heating or cooling.
- Displays Outdoor Temperature*
- Dual Fuel capable - swith-over to fossil fuel heating and increase energy efficiency and savings




a

DP732T Touchscreen 7-Day Programmable Thermostat Up to 3 Stage Heat / 2 Stage Cool Conventional or Heat Pump System Power Only

Features:

- Large, dot-matrix TRUE TOUCH-SCREEN with adjustable contrast
- 7-Day PROGRAMMABLE with 4 events per day and a COPY option for each day.
- Patented ENERGY WATCH, monitors the KWH consumption and dollar cost of operating the HVAC system.
- Filter Monitor indicates when to change air filter
- INSTALLER MESSAGE provides handy reminder for service or contact in case of a heating or cooling emergency.
- Security feature prevents operating thermostat without entering 4-digit PIN
- AUTOMATIC CHANGEOVER mode - no need to manually switch between heating or cooling.
- Displays Outdoor Temperature*
- Dual Fuel capable - swith-over to fossil fuel heating and increase energy efficiency and savings
- DEHUMIDIFICATION
- AUTOMATIC HUMIDITY CONTROL based upon outdoor temperature*



Specifications:

Pre-programmed with Four Adjustable Heating and Four Adjustable Cooling Programs for Weekdays, and Four Adjustable Heating Programs and Four Adjustable Cooling Programs for Weekends.

Electrical Ratings: 24 VAC Class 2 Maximum 2 Amps.

Temperature Accuracy: ±1°F (±0.5°C).

Humidity Accuracy: ±5%RH.

Moisture and Dust: meets IP20.

Operating Humidity: 20% to 90% non-condensing.

Operating Temperature: +23°F to +122°F (-5°C to +45°C).

Storage Temperature: -4°F to +140°F (-20°C to +60°C).

Electrical Immunity: meets relevant CE specifications.

Terminals: RC, RH, C, Y1, Y2, G, W2, O/B/W, DH, H, 11**, 12**

*PurePro® Outdoor Wireless Temperature Sensor Kit

Accurately displays current outdoor temperature and enables dual fuel capability on the PurePro DP721T & DP732T thermostats.

Mfr#: WTR064 Wireless Transmitter Webb #: 425736

**Terminals are not used.

PurePro®
1 Bon Terrain Drive
Amherst, NH 03031

PurePro®