


FUEL OIL FILTER REFILL CARTRIDGES



Features

88-CRW & 101W

- | High quality wool felt filter elements that remove all solid contaminants.
- | Crafted with special “step design” wool felt.
- | Step design element offers largest dirt capacity with true depth filtration.
- | Special center core bond treatment eliminates line.
- | Micronic filtration suited to the smallest oil burner nozzle.
- | For Models 77FW and 99FW, they offer unsurpassed quality and dependability.

RF-1W, RF-2W, RF-4W Series

- | Crafted with quality from continuous spun Rayon fibers.
- | Exclusive gear tooth design for maximum surface area.
- | Enhanced depth filtration.
- | 16-tooth gear design of the RF-Series rayon elements provides exceptional performance.
- | The RF-Series has a third more surface area.
- | The RF-Series has 20% more volume than the competitive product.
- | RF-1W is UL-Listed for the 1A-25A/Unifilter 77.
- | RF-2W is listed for the 2A-700A/99.
- | RF-4W is designed to fit other filter brands.



RF-1W Series Specifications

Surface Area	52 Sq. In.
Volume	12 Cu. In.
Firing Rate	10 GPH
Clean Pressure Drop	0.4 In. Hg.
Ending Pressure Drop	10.0 In. Hg.
Dirt Capacity (Test Contaminant)	1.4 Oz.
Filtration Depth	Medium

PurePro Cartridge Cross Reference Chart

PurePro Replacement Elements	Will Fit
88-CRW or RF-1W	F.W. Webb 77W, General 1A-25A, Unifilter 77, Sears 8055, Sid Harvey XF-25/264, Mitco 264, AutoFlo F-300, Federal A-77 and Westwood S-254
101W or RF-2W	General 2A-700A, Unifilter 101, Sid Harvey XF-1/265, Mitco 265, AutoFlo F-400 and Westwood S-254, F.W. Webb 99W
RF-4W	Fulflo B4, AS4, & FB4

PurePro®

1 Bon Terrain Drive
Amherst, NH 03031

PurePro®